



	MODEL	VOLTAGE (DC)	CRANKING AMPS (CA)	PEAK AMPS (PA)	CABLE LENGTH	CABLE CROSS SECTION	AUTOMATIC CHARGER	NET WEIGHT	DIMENSIONS
861044	MINI 12V-440CA	12	440	1600	0,6 m	25 mm ²	1,3 A	6 kg	360 x 130 x 240
861001	MICRO 12V-700CA	12	700	1860	1,3 m	25 mm ²	1,3 A	9,5 kg	375 x 110 x 320
861003	MICRO 12V700CA - Moto clamps	12	700	1860	1,3 m	25 mm ²	1,3 A	9,3 kg	375 x 110 x 320
861002	MICRO 12V800CA	12	800	2370	1,3 m	25 mm ²	2 A	9,5 kg	375 x 110 x 320
861011	MICRO 12V1000CA	12	1000	2960	1,3 m	25 mm ²	2 A	11 kg	375 x 110 x 320
860003	SOS 12V-1200CA	12	1200	3100	1,5 m	35 mm ²	2A	14,5 kg	450 x 130 x 390
861007	SOS 12V-1600CA	12	1600	3875	1,5 m	35 mm ²	2 A	18 kg	450 x 130 x 390
761001	SOS 12/24V-1400/700CA	12/24	1400/700	3720/1860	1,35 m	35 mm ²	4 A	20,5 kg	530 x 160 x 480
761006	SOS 12/24V-1600/800CA	12/24	1600/800	4740/2370	1,35 m	35 mm ²	4 A	20,5 kg	530 x 160 x 480
760008	SOS 12/24V-2400/1200CA	12/24	2400/1200	6200/3100	1,35 m	50 mm ²	4 A	24,8 kg	530 x 160 x 480
760005	SOS 24V 1200CA	24	1200	3100	1,35 m	50 mm ²	3,5 A	24,8 kg	530 x 160 x 480
960000	SOS MOBILE 12/24V-3200/1600CA	12/24	3200/1600	7750/3875	1,95 m	70 mm ²	10 A	55 kg	470 x 340 x 970
960001	SOS MOBILE 12/24V-6400/3200CA	12/24	6400/3200	15550/7750	1,95 m	70 mm ²	10 A	68,5 kg	470 x 340 x 970
960002	SOS MOBILE 24V-1600CA	24	1600	3875	1,95 m	70 mm ²	3,5 A	54 kg	470 x 340 x 970
960003	SOS MOBILE 24V-3200CA	24	3200	7750	1,95 m	70 mm ²	14 A	72,5 kg	470 x 340 x 970
860011	SOS 6V 850CA	6	850	2520	1,50 m	35 mm ²	0,8 A	16,5 kg	450 x 130 x 390
860000	SOS 6/12V 1700/850CA	6/12	1750/850	5040/2520	1,50 m	35 mm ²	1,3 A	25,5 kg	450 x 130 x 390