



H = Height, W = Width, L = Length



## SmartCharge 4A

A very userfriendly battery charger who is solving most of the charging jobs at home, in your caravan or your boat and for more professional jobs. SmartCharge represents the latest technology within battery charging which will give the battery optimum life.

A variety of SmartCharge accessories is available.

DEFA AS is conforming to the requirements of both ISO 9001-2008, ISO 14001:2004 and OHSAS 18001:2007. In addition to this, our engine heaters and cables are conforming to the requirements of ISO/TS 16949:2002.

### Technical specifications

Input voltage [VAC, Hz]	230, 50-60
Charge power, max [W]	60
Inverse current [mA]	< 1
Output voltage [VDC]	14,4/14,7
Operating temperature [°C]	-40 ~ +40
Cooling	air
Type of batteries	All types of lead/acid, AGM and GEL, open and closed.
Battery size [V/Ah]	12/2-110
IP rating [IP]	65
Isolation class [cl]	II
L/W/H [mm]	210x90x54
Weight, brutto [kg]	0,735
Certifications	EN60335-1 EN60355-2-29 EN 61204-3 EN61000-3-3 EN61000-3-2

### Item number

701515

Single pack only.

### Use

Take time to read the user manual and follow the instructions before using the charger!

### Functions

- Backlit user friendly interface and display.
- Adapts automatically to the size of your battery.
- A meter to easily read the actual power level of your battery.
- Integrated cable management.
- It will never over-charge your battery.
- Temperature compensated charging cycle.